



30-Day Android Challenge

From Basics to Advanced

(Expert-Level Deconstruction 📱)

Day 7

Broadcasts

Broadcast Receivers

The Ultimate Broadcast Receivers Masterclass –
Architecture, Performance, System & Code 🚀



Esmaeeil Moradi

@esmaeeil-moradi700

Day 7



The Ultimate Broadcast Receivers Masterclass – Architecture, Performance, System & Code

Welcome to the community of Android architects and seasoned enthusiasts!

Hello again to all senior engineers, future architects, and enthusiastic Android developers! 🙌


Continuing our 30-day challenge, we've reached Day 7 and one of the most fundamental yet challenging Android concepts: Broadcasts & Broadcast Receivers. In previous posts, we covered the basics and practical examples. Today, based on your request for higher-level insights and deeper details, we'll dive into a strategic analysis of this mechanism from the perspective of a system architect and with an eye on AOSP. Today's discussion is for those who want to master not just the how, but the why and the internal workings and system implications.



Esmaeel Moradi

@esmaeel-moradi700

Quick Refresher with Examples:



Before diving deep, let's quickly review receiver types with code:

Static Receiver (Manifest-Declared):

For critical system events like BOOT_COMPLETED. Works even when your app is closed (respecting Android 8+ limitations).

```
<receiver
  android:name=".MyBootReceiver"
  android:enabled="true"
  android:exported="true"> <intent-filter>
  <action
    android:name="android.intent.action.BOOT_COMPLETED" />
    <uses-permission
      android:name="android.permission.RECEIVE_BOOT_COMPLETED" />
    </intent-filter>
  </receiver>
```



Esmaeel Moradi
@esmaeeil-moradi700

Dynamic Receiver (Context-Registered):

For events relevant only when a component (like an Activity) is active, such as reacting to airplane mode changes.

```
// In an Activity or Service
private val airplaneModeReceiver = object : BroadcastReceiver() {
    override fun onReceive(context: Context?, intent: Intent?) {
        val isAirplaneModeOn = intent?.getBooleanExtra("state", false) ?: return
        // ... process airplane mode change ...
        Log.d("AirplaneMode", "Airplane mode state changed: $isAirplaneModeOn")
    }
}

override fun onResume() {
    super.onResume()
    val filter = IntentFilter(Intent.ACTION_AIRPLANE_MODE_CHANGED)
    registerReceiver(airplaneModeReceiver, filter) // Register receiver
}

override fun onPause() {
    super.onPause()
    unregisterReceiver(airplaneModeReceiver) // Unregister to prevent memory leak
}
```



Esmaeel Moradi

@esmaeel-moradi700

Comparison Table: Static vs. Dynamic Receivers:

Feature	Static Receiver (Manifest-Declared)	Dynamic Receiver (Context-Registered)
Lifetime	Even when app is inactive (with limits)	Only while the registering component is active
Registration	In Manifest (compile-time)	In Code (runtime), requires manual unregister
Context Dependency	No (directly)	Yes (depends on the registering Context)
Resource Usage	Medium (potential to wake up app)	Low (active only when needed)
Flexibility	Limited	High (full control in code)
API Limits	Strict limits for Implicit since API 26+	No inherent limits (but follows Lifecycle)
Security	Needs careful exported & permission setup	Better control via Context and active time
Example Use Case	Startup after boot (BOOT_COMPLETED)	UI changes based on runtime events



Esmaeel Moradi
@esmaeel-moradi700

Performance Optimization: Beyond goAsync

We all know onReceive must be fast. But true optimization means understanding the bottlenecks:

- **Resolution Cost & Wake-up:** The system incurs costs finding suitable receivers for each broadcast (static or dynamic). More receivers and filters mean higher costs. Sending unnecessary broadcasts or using overly broad filters creates overhead.
- **WakeLock Management:** The system automatically holds a short WakeLock to execute onReceive. goAsync extends this WakeLock for you slightly (around 10 seconds) to perform light background work . But remember:
 - This time is limited and not guaranteed.
 - Forgetting pendingResult.finish() wastes resources and negatively impacts battery life.
 - For longer or guaranteed tasks, WorkManager, with its smarter WakeLock management and opportunistic execution, is a better choice.



Esmaeel Moradi
@esmaeel-moradi700



```
// Correct use of goAsync with Coroutines for lightweight background work
override fun onReceive(context: Context, intent: Intent) {
    val pendingResult = goAsync() // Obtain PendingResult

    CoroutineScope(Dispatchers.IO).launch { // Run work on a background thread
        try {
            Log.d("ReceiverPerf", "Starting background work...")

            // Perform a quick, time-consuming operation (e.g., saving
to SharedPreferences)
            delay(1000) // Simulate work

            Log.d("ReceiverPerf", "Background work finished.")
        } finally {
            pendingResult.finish() // Mark work as finished and release WakeLock
        }
    }
}
```

```
// Offloading work to WorkManager from within a Receiver
override fun onReceive(context: Context, intent: Intent) {
    Log.d("ReceiverTrigger", "Received broadcast, enqueueing WorkManager task.")
    val inputData = workDataOf("DATA_KEY" to intent.getStringExtra("payload"))

    val workRequest = OneTimeWorkRequestBuilder<MyDataProcessingWorker>()
        .setInputData(inputData)
        .build()

    WorkManager.getInstance(context).enqueue(workRequest)
}
```



Esmaeel Moradi
@esmaeeil-moradi700

- **Risk of Broadcast Storms:**

A scenario where an event triggers a broadcast, and its receiver triggers the same (or another triggering broadcast), creating a vicious cycle. This can cripple the system. —————→

- **Prevention:** Precise filtering, using Debouncing or Throttling mechanisms in receivers, avoiding sending unnecessary broadcasts from within onReceive, and using LocalBroadcastManager or alternatives for internal communication

- **Advanced Conditional Registration:**

Register the receiver only when truly needed. This isn't limited to Activity Lifecycle; it could be based on application state, user settings, or even network status.

```
// Conditional registration based on need
private var isNetworkReceiverRegistered = false
// ...
fun updateNetworkMonitoring(context: Context, enable: Boolean) {
    if (enable && !isNetworkReceiverRegistered) {
        val filter = IntentFilter(ConnectivityManager.CONNECTIVITY_ACTION)
        context.registerReceiver(networkChangeReceiver, filter)
        isNetworkReceiverRegistered = true
        Log.d("ConditionalReg", "Network receiver registered.")
    } else if (!enable && isNetworkReceiverRegistered) {
        context.unregisterReceiver(networkChangeReceiver)
        isNetworkReceiverRegistered = false
        Log.d("ConditionalReg", "Network receiver unregistered.")
    }
}
```



Esmaeel Moradi

@esmaeeil-moradi700

Architectural Patterns & Broadcasts:



Broadcasts can play a role in various architectural patterns, but with caveats:

- Internal Event Bus: Using LocalBroadcastManager (or better, Flow/LiveData) to implement the Publish-Subscribe pattern within the app.
 - Pros: Excellent decoupling between components (e.g., a Service doesn't know about the Activity, it just publishes an event).
 - Cons: Debugging the data flow can become difficult; potential for hidden dependencies on events. Must be used carefully and structuredly.

```
// Sending an internal event with LocalBroadcastManager (example; modern alter
val localIntent = Intent("custom-event-data-updated").putExtra("item_id", 42)
LocalBroadcastManager.getInstance(context).sendBroadcast(localIntent)

// Receiving the internal event
private val dataUpdateReceiver = object : BroadcastReceiver() {
    override fun onReceive(context: Context?, intent: Intent?) {
        val id = intent?.getIntExtra("item_id", -1)
        Log.d("LocalEventBus", "Received internal event for item: $id")
        // ... React to the event ...
    }
}

// Dynamically register/unregister this receiver in the appropriate Lifecycle
// LocalBroadcastManager.getInstance(context).registerReceiver(...)
// LocalBroadcastManager.getInstance(context).unregisterReceiver(...)
```



Esmaeel Moradi
@esmaeeil-moradi700

- **Microservice Architecture on Android?**



An attractive idea where each core feature (payment, analytics, ...) is implemented in a separate Receiver or Service, communicating via Broadcasts.

- Challenges: Process management and IPC have overhead on Android. Maintaining state and coordination between these "services" is complex. Might be suitable for very large, specific apps, but typically, intra-process modularization patterns (like Feature Modules) are more efficient.

```
// Example structure of services (highly simplified)

class PaymentServiceReceiver : BroadcastReceiver() {
    override fun onReceive(context: Context, intent: Intent) {
        // Process payment logic here
    }
}

class AnalyticsServiceReceiver : BroadcastReceiver() {
    override fun onReceive(context: Context, intent: Intent) {
        // Send analytics data here
    }
}

// Invoking services by sending secure, explicit Broadcasts
```



Esmaeel Moradi
@esmaeel-moradi700



Place in Clean Architecture/MVVM/MVI:

- System broadcasts are usually received in the Data layer or the outer Framework layer. Their information is extracted and passed to the Domain or Use Case layers. Results reach the Presentation layer (ViewModel) via reactive mechanisms (like Flow/LiveData). Using system broadcasts directly in the Domain or ViewModel layers is generally discouraged (violates layer separation). Local Broadcasts (or alternatives) can be used for communication between ViewModels or UI components (**with caution**).



Esmaeel Moradi

@esmaeel-moradi700

Security Deep Dive:




Permission Protection Levels (`protectionLevel`):

- "normal": User grants permission at install time.
- "dangerous": User must grant permission at runtime (Runtime Permission).
- "signature": Only apps signed with the same key can get the permission (ideal for communication between your own apps).
- "signatureOrSystem": Like signature, plus system apps.
- Choosing the right level for custom permissions is crucial.



Esmaeel Moradi

@esmaeel-moradi700



```
<permission android:name="com.example.myapplication.permission.ACCESS_DATA"
            android:protectionLevel="signature" />

<receiver
    android:name=".MySecureReceiver"
    android:permission="com.example.myapplication.permission.ACCESS_DATA"
    android:exported="true"> <intent-filter>
    <action android:name="com.example.myapplication.ACTION_PROCESS_DATA" />
    </intent-filter>
</receiver>
```

```
// Sending a Broadcast that requires the receiver to have a specific permission
val intent = Intent("com.example.myapplication.ACTION_PROCESS_DATA").apply {
    putExtra("payload", "sensitive_info")
}
// Only receivers with the specified permission will receive this broadcast
context.sendBroadcast(
    intent,
    "com.example.myapplication.permission.ACCESS_DATA" // Receiver's required permission
)
Log.d("Security", "Sent secure broadcast requiring receiver permission.")

// Sending a Local Broadcast for secure internal communication (no
// permission needed)
val localIntent = Intent("com.example.myapplication.LOCAL_ACTION")
LocalBroadcastManager.getInstance(context).sendBroadcast(localIntent)
```



Esmaeel Moradi
@esmaeel-moradi700



Beyond Permissions:

- **Intent Sniffing:** Even with correct permissions, malicious apps (especially on older Android versions or rooted devices) might be able to eavesdrop on broadcasted Intents. Avoid sending sensitive data in non-local broadcasts.
- **Data Validation in onReceive:** Always validate data within the Intent, even if the broadcast came from a trusted source (with permission or Explicit Intent). The sender might have its own bugs.
- **Risk of Exported Components:** We reiterate: any Receiver (or Activity, Service, Provider) that is exported="true" and not properly protected (with strong permission) **is an open door for attacks.**
- **INTERACT_ACROSS_USERS Permission:** Required for sending broadcasts between different user profiles on a device, and has its own restrictions.
- **Fuzz Testing:** Sending manipulated and unexpected Intents to exported Receivers to find crashes or security vulnerabilities .



Esmaeel Moradi
@esmaeel-moradi700



AOSP Exploration & System Interactions:

- **Queue Details & Prioritization:**
 - **AMS actually has three main queues:** Foreground (for broadcasts with FLAG_RECEIVER_FOREGROUND or sent from a foreground app), Background, and Offload (for low-priority broadcasts that can be delayed by the system for performance improvement - Android 10+).
 - **Priority isn't just android:** priority in the manifest. The sender app's state, Intent flags (like FLAG_RECEIVER_REGISTERED_ONLY which sends only to dynamic receivers), permissions, and even Doze and App Standby policies play a role in delivery order and timing.



Esmaeel Moradi
@esmaeel-moradi700




- **Background Execution Limits:** Android severely restricts background execution. Most implicit broadcasts no longer activate static receivers. Even dynamic receivers registered in background services might face restrictions. WorkManager is the standard solution for reliable background work.
- **DOS Prevention:** AMS itself has mechanisms like Rate Limiting and caps on pending broadcasts per app to prevent Denial of Service attacks.
 - **Key Points in AOSP Code:**
 - BroadcastQueue.java: Queuing and prioritization logic.
 - BroadcastFilter.java: Matching Intents with receiver filters .
 - ActivityManagerService.java: Core methods like registerReceiver, sendBroadcast, broadcastIntentLocked, and verifyBroadcastLocked (for checking permissions).



Esmaeel Moradi
@esmaeeil-moradi700

Specific Broadcasts & Edge Cases: ✨



- **sendOrderedBroadcast:** Unlike `sendBroadcast` (parallel), this sends the broadcast serially to receivers in priority order (high to low).

Each receiver can:

1. Pass results to the next receiver (`setResultData`, `setResultCode`, ...).
2. Prevent the message from reaching subsequent receivers (`abortBroadcast()`).
3. Use Case: Scenarios like SMS interception (before reaching the default app) or executing a chain of operations with priority.


- **sendStickyBroadcast (Deprecated!):** Previously used for broadcasts whose last value "stuck" in the system, so that receivers registering later would immediately get that last value (like battery status). Completely deprecated due to severe security issues (any app could read the last state or even send a fake sticky). Such states should now be managed differently (e.g., `StateFlow` or direct querying).
- **Receivers in Safe Mode:** By default, receivers from user-installed apps do not run in Android's Safe Mode (unless it's a system app with the `ApplicationInfo.FLAG_SYSTEM` flag).



Esmaeel Moradi

@esmaeel-moradi700

Broadcasts vs. Modern Alternatives: Strategic Choice 🤔



- **Broadcast Receiver: Best choice for:**

1. Reacting to system events that lack a specific dedicated API or need reception even when the app is inactive (like `BOOT_COMPLETED` with a static receiver).
2. Simple, public one-to-many communication at the system level (with extreme security caution).
3. Events requiring ordered reception and abort capability.

- **WorkManager: Best choice for:**

1. Guaranteed, deferrable, and constraint-based background work (e.g., requiring network, charging, storage).
2. Replacing most static receivers that reacted to system events (like network connectivity).

- **LiveData / Kotlin Flow (StateFlow, SharedFlow): Best choice for:**

1. Publishing State or Single Events in a Lifecycle-aware manner within the application, especially for UI updates.
2. Replacing LocalBroadcastManager for secure and efficient internal communication.
3. Implementing the Observer pattern modernly and compatible with Coroutines.


- **NetworkCallback API:**

1. Modern, more efficient alternative for detailed network state monitoring compared to the `CONNECTIVITY_ACTION` broadcast (especially for foreground apps).



Esmaeel Moradi
@esmaeel-moradi700

Professional Best Practices:



To use Broadcast Receivers optimally and sustainably, follow these key practices:

- **Lifecycle Management:**

1. Always unregister (unregisterReceiver) Dynamic Receivers in the corresponding lifecycle method where they were registered (usually onPause or onDestroy, or the equivalent in Services/Fragments) to prevent Memory Leaks.
2. When registering dynamically (Context.registerReceiver), you can specify a Handler to have onReceive execute on that Handler's thread (e.g., a background thread). This is useful to avoid blocking the main thread, but WakeLock management and receiver termination become your responsibility.

- **Performance Optimization:**

1. As emphasized, use goAsync() for slightly longer operations in onReceive and always call pendingResult.finish().
2. Strictly avoid sending unnecessary Broadcasts. Every broadcast costs the system. Use more efficient alternatives for internal communication.


- **Version Compatibility:**

1. To receive BOOT_COMPLETED, ensure you request the android.permission.RECEIVE_BOOT_COMPLETED permission in the Manifest .
2. Given the strict limitations on static receivers since Android 8+, use WorkManager for most background tasks previously handled by static receivers [104]. WorkManager is designed for cross-version compatibility and optimal resource management.



Esmaeel Moradi
@esmaeel-moradi700

? Advanced Interview Insights



- What is the exact broadcast prioritization mechanism in ActivityManagerService (AMS)? (Beyond android:priority)
- How can one effectively prevent Broadcast Storms, and what tools exist for diagnosing them?
- How does goAsync() work internally? How is the WakeLock managed, and what are its real limitations?
- What are the key differences between sendBroadcast, sendOrderedBroadcast, and LocalBroadcastManager.sendBroadcast in terms of performance, security, and use cases?
- What are the main security risks of using exported="true" for Receivers, and how can they be fully mitigated? (Beyond just setting permissions)
- In which scenarios is using a Static Broadcast Receiver (respecting limitations) still reasonable, and why isn't WorkManager always a suitable replacement?
- How do Background Execution Limits (Android 8+) affect dynamic receivers registered in background Services?
- How does AMS protect the system against Denial of Service attacks via excessive broadcast sending?
- (Scenario) How would you design secure and efficient communication between two separate apps (both owned by you) using Broadcasts? (protectionLevel, signature, Explicit Intent, ...)
- How are receivers managed in Safe Mode, and what is the role of the ApplicationInfo.FLAG_SYSTEM flag?



Esmaeel Moradi

@esmaeeil-moradi700




Architectural Challenge for Architects

Given the current AOSP broadcast architecture, how could broadcast delivery performance be optimized on a device with hundreds of installed apps, each having dozens of receivers? Could changing AMS internal data structures (e.g., using a TreeMap instead of a list for filters) or more advanced matching mechanisms be effective? What would be the trade-offs?



Esmaeeil Moradi

@esmaeeil-moradi700



Final Summary:

Mastery of Broadcast Receivers isn't just about knowing the API; it's about a deep understanding of performance impacts, security considerations, appropriate architectural patterns, system limitations, Best Practices, and modern alternatives. This extremely detailed post aimed to guide you on this path by combining high-level explanations with numerous practical code examples and key insights. Hopefully, this comprehensive masterclass has been beneficial!



Esmaeel Moradi
@esmaeeil-moradi700

Looking forward to your
insights and experiences!
Let's elevate Android
development together.



LEAVE A COMMENT BELOW



Esmaeeil Moradi

@esmaeeil-moradi700